

Hangzhou Easy Electric Wire and Cable Co., LTD

Add: Room 305, Building 2, No. 380 Fangxin Road, Hangzhou, China

www.eescable.com

TEST REPORT

	Mode1	ACSS 26*2	2.89+7	*2.25 Number	221	2058
NO.		Test items	unit	standard requirement	test result	single judgment
1	structure size					
	Number of aluminum single wires		root	26	26	
	Number of steel single wires		root	7	7	
	Aluminum single wire diameter		mm	2.89+\-0.03	2.878 2.895 2.891	\checkmark
	Steel single wire diameter		mm	2.25+\-0.0	2.251 2.255 2.253	
	Wire outer diameter		mm	22.4	18.31	
2	Pitch ratio					
	outermost layer (aluminum)		times	10-13	11.82	
	Proximal outer layer (aluminum)		times	10-16	13.27	
	6 layers (s	steel strands)	times	16-26	18.55	
3	twist			right	pass	V
4	Exterior			The surface of the stranded wire shall not have visible defects, such as obvious scratches, indentations, etc., and shall not have any defects that are disproportionate to good goods.	pass	\checkmark
5	Aluminum wi	re performance				
	20°C singl	le wire DC resistance	nΩ•m	≦27.889	27.14	
1	Tensile str	rength before	Mpa	60-95	72 69 75	\checkmark
	winding tes	st		At a speed not exceeding 60r/min, the 1D core is wound for 8 turns, backed up by 6 turns, and then tightly wound for 8 turns. The duralumin wire should not break.	pass	\checkmark

6	Steel wire properties				\checkmark
	Minimum tensile strength	Mpa	1450	1633	
	1% Elongation Stress	Mpa	1310	1389	
	250mm gauge length elongation	%	≧3%	4	
	Zinc coating	g/m^2	≧220	282	
	winding test		The galvanized steel wire is tightly wound on the mandrel (1 times the diameter of the conductor) for 8 turns at a speed not exceeding 15r/min, and the galvanized steel wire does not break	pass	\checkmark
7	Oiled weight	kg/km	-	-	-
	Oiled - except for the single line of the outer layer, the inner layer is fully oiled		_	_	-
	oil drop point	°C	-	-	-
8	Overall performance				
	Weight per unit length	kg/km	6 89	688	\checkmark
	breaking load	kN	49.82	54.17	
	20°C DC resistance	Ω/km	≦0.1637	0. 1602	

Note: " \checkmark " means that the item is qualified " \times " means that the item is unqualified "-" means that the item does not require testing

Conclusion: The tested test items meet the requirements of the technical agreement and pass the inspection.

Inspectors: Fengmei Zhang

audit: Meishuai Liu

Date: 2023.1.9

杭州益睿电线电缆有限公司 HANGZHOU EASY ELECTRIC VIRE AND CABLE CO., LTD.