

Easy Electric Supply Limited

Add: Room 305, Building 2, No. 380 Fengxin Road, Hangzhou, China

www.eescable.com

TEST REPORT

Products	AAC 336. 4MCM '	'Tulip"	Size	19*3.38	
Standard	ASTM B230 B231	Invoice No.	20230423002	Date	2023.04.23
NO.	Item	Standards and Requirements		Test Results	Evaluation
1	Structure				
1-1	Number Of Wire	19		19	Qualified
1-2	Dia. Of Wire	3.38mm±0.034		3.38mm	Qualified
1-3	Min. Tensile Strength	≥170N		185N	Qualified
1-4	Elongation(250mm)	1.8%		2.1%	Qualified
1-5	Diameter Of Conductor	16.9mm±0.17		17.0mm	Qualified
1-6	Outer Stranding Direction Of Conductor	Rightward		Rightward	Qualified
1-7	Lay Ratio Of Conductor	10-14		13.5	Qualified
1-8	20℃ Max D.C Resistivity	≪0.028172Ω.m		0.02789	Qualified
2	Surface Of Conductor				
2-1	Surface Quality	The Surface Shall Be Smooth, Stranded Compactly, No Missing, Broken, Jumping or Loosing Strands.		Smooth, Compact	Qualified
3	Conductor Properties				
3-1	Conductor resistance at 20℃	≪0.1686 Ω /km		0.1674	Qualified
3-2	Overall reaking force	27.3KN		29.53KN	Qualified
3-3	Grease	IEC Case 1		IEC Case 1	Qualified
3-4	Cable weight	470±9.4kg/km		472.3kg/km	Qualified

Tested by: Shaoqiong He

益瑞電力供應有限公司 recked by: Guohui Xu

Hangzhou Easy Electric Wire and Cable Co., LTD

Add: Room B415, Future Technology Park, No.7 Long Tan Road Hangzhou, China

EASY ELECTRIC SUPPLY LIMITED