

## Hangzhou Easy Electric Wire and Cable Co.,LTD

Add: Room 305, Building 2, No. 380 Fengxin Road, Hangzhou, China

www.eescable.com

## TEST REPORT

Products	HDBC 29	<	Size	19*1.	4
Standard	ASTM B2 ASTM B8	Invoice No.	20230105003	Date	2023.01.05
NO.	Item	Standards and Requirements		Test Results	Evaluation
1	Structure				
1-1	Number Of Wire	19		19	Qualified
1-2	Diameter of wire	1.4mm±0.014		1.41	Qualified
1-4	Diameter Of Conductor	7.0mm		7.0	Qualified
1-5	Outer stranding	Right hand		Right hand	Qualified
1-6	Minimum tensile strength of wire	415N/MM2		432	Qualified
2	Surface Of Conductor				
2-1	Surface Quality	The Surface Shall Be Smooth, Stranded Compactly, No Missing, Broken, Jumping or Loosing Strands.		Smooth, Compact	Qualified
3	Conductor Properties				
3-1	20℃ Max D.C Resistance	≤0.617 Ω /km		0.601	Qualified
3-2	Min. Breaking Load	12.1KN		13.4KN	Qualified
3-3	Approximate total weight of cable	263.7 $\pm$ 5.3kg/km		264. 2	Qualified

Tested by: Shaoqiong He

Checked by: Guohui Xu

杭州益睿电线电缆有限公司 BANGZHOU EASY ELECTRIC VIRE AND CABLE CO., LTD.