


## SZ13-35KV

Oil Immersed Power Transformer



Standard	IEC60076-1, IEC60076-2, IEC60076-3, IEC60076-5, IEC60076-10						
Rated capacity (kVA)	2000	2500	3150	4000	5000	6300	8000
High Voltage	35kV, 38.5kV, Or other						
Tapping Range	±3x2.5%						
Low Voltage	6.3kV, 10.5kV, Or other						
Connection of transformer winding	Yd11						YNd11
No-load Loss (W)	2300	2720	3230	3870	4640	5630	7870
Load Loss (W) 145°C	19200	20600	24700	29100	34200	36700	40600
No-load Current (%)	0.5	0.5	0.45	0.45	0.45	0.45	0.4
Impedance Voltage (%)	6.5	6.5	7.0	7.0	7.0	8.0	8.0

Standard	IEC60076-1, IEC60076-2, IEC60076-3, IEC60076-5, IEC60076-10					
Rated capacity (kVA)	10000	12500	16000	20000	25000	31500
High Voltage	35kV, 38.5kV, Or other					
Tapping Range	±3x2.5%					
Low Voltage	6.3kV, 10.5kV, Or other					
Connection of transformer winding	YNd11					
No-load Loss (W)	9280	10900	13100	15500	18300	21800
Load Loss (W) 145°C	48000	56800	70300	82100	97800	11600
No-load Current (%)	0.4	0.35	0.35	0.35	0.3	0.3
Impedance Voltage (%)	8.0	8.0	8.0	8.0	10.0	10.0